IN THE CLAIMS:

Please replace claims 1-38 with the following claims:

1. (New) A system for interfacing with an on-board diagnostic computer in a vehicle, wherein the on-board diagnostic computer is configured to monitor a set of operational characteristics of the vehicle, the system comprising:

a wireless appliance which during use communicates with the vehicle's on-board diagnostic computer, said wireless appliance comprising (i) a wireless communication component and (ii) a data-collection component,

said wireless communication component configured to wirelessly receive a schema identifying a subset of the set of operational characteristics that are monitored by the on-board diagnostic computer,

said data-collection component configured to process the received schema and to collect from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema,

said wireless communication component being further configured to wirelessly transmit said collected data,

wherein the schema identifies an address of an operational characteristic for which data is to be collected from the vehicle's on-board diagnostic computer,

wherein the schema includes a field that describes a time or frequency at which the data-

collection component queries the vehicle's on-board diagnostic computer,

wherein the operational characteristics include at least one of the following: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature, engine coolant temperature, intakemanifold pressure, engine-performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel-injector performance, spark-plug timing, and a status of an anti-lock braking system,

wherein the wireless appliance is configured to send an outgoing data packet that indicates a vehicle's location,

wherein the data-collection component is configured to repeatedly collect said data from the vehicle's on-board diagnostic computer at times determined by a first schedule specified in the schema, and

wherein the wireless communication component is configured to repeatedly wirelessly transmit the collected data at times determined by a second schedule specified in the schema.

2. (New) A system for interfacing with an on-board diagnostic computer in a vehicle, wherein the on-board diagnostic computer is configured to monitor a set of operational characteristics of the vehicle, the system comprising:

a wireless appliance which during use communicates with the vehicle's on-board diagnostic computer, said wireless appliance comprising (i) a wireless communication component and (ii) a data-collection component,

said wireless communication component configured to wirelessly receive a schema identifying a subset of the set of operational characteristics that are monitored by the on-board diagnostic computer,

said data-collection component configured to process the received schema and to collect from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema, and

said wireless communication component being further configured to wirelessly transmit said collected data.

- 3. (New) The system of claim 2, wherein the schema identifies an address of an operational characteristic for which data is to be collected from the vehicle's on-board diagnostic computer.
- 4. (New) The system of claim 2, wherein the schema comprises an address that describes a location of a diagnostic datum in a computer memory in the vehicle.
- 5. (New) The system of claim 2, wherein the schema comprises a field that describes a time or frequency at which the data-collection component queries the vehicle's onboard diagnostic computer.

- 6. (New) The system of claim 2, wherein the schema comprises a field that describes a time or frequency at which the data-transmission component transmits data.
 - 7. (New) The system of claim 2, wherein the schema is an ASCII or binary data file.
- 8. (New) The system of claim 2, wherein the operational characteristics include at least one of the following: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature, engine coolant temperature, intake-manifold pressure, engine-performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel-injector performance, spark-plug timing, and a status of an anti-lock braking system.
- 9. (New) The system of claim 2, wherein the wireless appliance is configured to send an outgoing data packet that indicates a vehicle's location.
- 10. (New) The system of claim 2, wherein the vehicle is selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.

- 11. (New) The system of claim 2, wherein the data-collection component is configured to repeatedly collect said data from the vehicle's on-board diagnostic computer at times determined by a first schedule.
- 12. (New) The system of claim 11, wherein the first schedule is specified in the schema.
- 13. (New) The system of claim 2, wherein the wireless communication component is configured to repeatedly wirelessly transmit the collected data at times determined by a first schedule.
- 14. (New) The system of claim 13, wherein the first schedule is specified in the schema.
 - 15. (New) A system for monitoring a set of vehicles, comprising:
- a host computer configured to host a web site that receives operational characteristics transmitted wirelessly from the set of vehicles,

said web site programmed to display on a first web interface operational characteristics of a single vehicle selected from among said set of vehicles,

said web site programmed to also display on a second web interface operational characteristics of multiple vehicles among said set of vehicles,

wherein said multiple vehicles are associated with a single entity.

- 16. (New) The system of claim 15, wherein the host computer is configured to wirelessly transmit a schema identifying a subset of a set of operational characteristics to be monitored by an on-board diagnostic computer of a target vehicle.
- 17. (New) The system of claim 16, wherein the web site includes a schema selector to select the schema to be transmitted.
- 18. (New) The system of claim 15, wherein the first web interface comprises a first web page that displays a vehicle diagnostic datum.
- 19. (New) The system of claim 18, wherein the first web page comprises data fields describing: (i) a name of a diagnostic datum; (ii) units corresponding to the diagnostic datum; and (iii) a numerical value corresponding to the diagnostic datum.
 - 20. (New) The system of claim 19, wherein the first web page further comprises

multiple sets of diagnostic data associated with the single vehicle.

- 21. (New) The system of claim 18, wherein the first web page includes a graphical representation of a set of diagnostic data.
- 22. (New) The system of claim 15, wherein the web site further comprises a database component.
- 23. (New) The system of claim 15, wherein the web site further comprises a login web page programmed to accept user name and password inputs of a user.
- 24. (New) The system of claim 23, wherein the web site is configured to determine whether the user is associated with the first or second web interface.
- 25. (New) The system of claim 15, wherein the multiple vehicles are each associated with a single user.
 - 26. (New) The system of claim 15, wherein the web site is configured to be displayed

on a hand-held device.

- 27. (New) The system of claim 26, wherein the hand-held device comprises a cellular telephone, computer, or personal digital assistant (PDA).
- 28. (New) The system of claim 15, wherein the host computer is further configured to send an electronic communication including at least a portion of the operational characteristics of the single vehicle or multiple vehicles.
- 29. (New) The system of claim 15, wherein the host computer is further configured to analyze a location of the single vehicle and display the location on at least one map.
- 30. (New) The system of claim 15, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 31. (New) The system of claim 15, wherein the set of vehicles includes a fleet of vehicles.

32. (New) A system for monitoring a set of vehicles, comprising:

a host computer configured to host a web site that receives operational characteristics transmitted wirelessly from the set of vehicles,

said web site programmed to display on a first web interface operational characteristics of a single vehicle selected from among said set of vehicles,

said web site programmed to also display on a second web interface operational characteristics of multiple vehicles among said set of vehicles,

wherein said multiple vehicles are associated with a single entity,

wherein the host computer is configured to wirelessly transmit a schema identifying a subset of a set of operational characteristics to be monitored by an on-board diagnostic computer of a target vehicle,

wherein the web site includes a schema selector to select the schema to be transmitted.

wherein the first web interface comprises a first web page that displays a vehicle diagnostic datum,

wherein the first web page comprises data fields describing: (i) a name of a diagnostic datum; (ii) units corresponding to the diagnostic datum; and (iii) a numerical value corresponding to the diagnostic datum,

wherein the first web page further comprises multiple sets of diagnostic data associated

with the single vehicle, and

wherein the host computer is further configured to send an electronic communication including at least a portion of the operational characteristics of the single vehicle or multiple vehicles.

33. (New) A system for monitoring a set of vehicles, comprising:

a host computer configured to wirelessly transmit a schema,

wherein the schema identifies a subset of a set of operational characteristics that are monitorable by an on-board diagnostic computer of a target vehicle among a set of vehicles, and

wherein the host computer is further configured to wirelessly receive collected vehicle data of the target vehicle, the collected data including the subset of monitorable operational characteristics identified in the transmitted schema.

- 34. (New) The system of claim 33, wherein the schema is associated with a predetermined group of vehicles.
- 35. (New) The system of claim 34, wherein the predetermined group of vehicles have at least one attribute in common.

- 36. (New) The system of claim 33, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 37. (New) A method of monitoring a set of operational characteristics of a vehicle, comprising:
- (a) wirelessly receiving, by a wireless appliance in a vehicle, a schema identifying a subset of a set of operational characteristics that are monitored by an on-board diagnostic computer of the vehicle;
 - (b) processing the received schema;
- (c) collecting from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema;
 - (d) wirelessly transmitting the collected data; and
 - (e) wirelessly transmitting data indicative of the vehicle's location,

wherein the schema identifies an address of an operational characteristic for which data is to be collected from the vehicle's on-board diagnostic computer,

wherein the schema comprises an address that describes a location of a diagnostic datum in a computer memory in the vehicle,

wherein the schema comprises a field that describes a time or frequency at which the data collecting occurs, and

wherein the operational characteristics include at least one of the following: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature, engine coolant temperature, intakemanifold pressure, engine-performance tuning parameters, alarm status, accelerometer status, cruise-control status, fuel-injector performance, spark-plug timing, and a status of an anti-lock braking system.

- 38. (New) A method of monitoring a set of operational characteristics of a vehicle, comprising:
- (a) wirelessly receiving, by a wireless appliance in a vehicle, a schema identifying a subset of a set of operational characteristics that are monitored by an on-board diagnostic computer of the vehicle;
 - (b) processing the received schema;
- (c) collecting from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema; and
 - (d) wirelessly transmitting the collected data.
 - 39. (New) The method of claim 38, wherein the schema identifies an address of an

operational characteristic for which data is to be collected from the vehicle's on-board diagnostic computer.

- 40. (New) The method of claim 38, wherein the schema comprises an address that describes a location of a diagnostic datum in a computer memory in the vehicle.
- 41. (New) The method of claim 38, wherein the schema comprises a field that describes a time or frequency at which the data collecting occurs.
- 42. (New) The method of claim 38, wherein the schema comprises a field that describes a time or frequency at which the data transmitting occurs.
- 43. (New) The method of claim 38, wherein the schema is an ASCII or binary data file.
- 44. (New) The method of claim 38, wherein the operational characteristics include at least one of the following: diagnostic trouble codes, vehicle speed, fuel level, fuel pressure, miles per gallon, engine RPM, mileage, oil pressure, oil temperature, tire pressure, tire temperature, engine coolant temperature, intake-manifold pressure, engine-performance tuning parameters,

alarm status, accelerometer status, cruise-control status, fuel-injector performance, spark-plug timing, and a status of an anti-lock braking system.

- 45. (New) The method of claim 38, further comprising wirelessly transmitting data indicative of the vehicle's location.
- 46. (New) The method of claim 38, wherein the vehicle is selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 47. (New) The method of claim 38, wherein collecting data includes repeatedly collecting data from the vehicle's on-board diagnostic computer at times determined by a first schedule.
- 48. (New) The method of claim 47, wherein the first schedule is specified in the schema.
- 49. (New) The method of claim 38, wherein transmitting the collected data includes repeatedly transmitting the collected data at times determined by a first schedule.

- 50. (New) The method of claim 49, wherein the first schedule is specified in the schema.
 - 51. (New) A method of monitoring a set of vehicles, comprising:
- (a) wirelessly receiving, by a host computer, operational characteristics of a set of vehicles;
- (b) displaying, on a first web interface of a web site, operational characteristics of a single vehicle selected from among said set of vehicles;
- (c) displaying, on a second web interface of the web site, operational characteristics of multiple vehicles among said set of vehicles; and
- (d) wirelessly transmitting a schema identifying a subset of a set of operational characteristics to be monitored by an on-board diagnostic computer of a target vehicle,

wherein said multiple vehicles are associated with a single entity,

wherein the web site includes a schema selector to select the schema to be transmitted,

wherein the first web interface comprises a first web page that displays a vehicle diagnostic datum,

wherein the first web page comprises data fields describing: (i) a name of a diagnostic datum; (ii) units corresponding to the diagnostic datum; and (iii) a numerical value

corresponding to the diagnostic datum,

wherein the first web page further comprises multiple sets of diagnostic data associated with the single vehicle,

wherein the web site further comprises a login web page programmed to accept user name and password inputs of a user, and

wherein the web site is configured to determine whether the user is associated with the first or second web interface.

- 52. (New) A method of monitoring a set of vehicles, comprising:
- (a) wirelessly receiving, by a host computer, operational characteristics of a set of vehicles;
- (b) displaying, on a first web interface of a web site, operational characteristics of a single vehicle selected from among said set of vehicles; and
- (c) displaying, on a second web interface of the web site, operational characteristics of multiple vehicles among said set of vehicles,

wherein said multiple vehicles are associated with a single entity.

53. (New) The method of claim 52, further comprising wirelessly transmitting a schema identifying a subset of a set of operational characteristics to be monitored by an on-board

diagnostic computer of a target vehicle.

- 54. (New) The method of claim 53, wherein the web site includes a schema selector to select the schema to be transmitted.
- 55. (New) The method of claim 52, wherein the first web interface comprises a first web page that displays a vehicle diagnostic datum.
- 56. (New) The method of claim 55, wherein the first web page comprises data fields describing: (i) a name of a diagnostic datum; (ii) units corresponding to the diagnostic datum; and (iii) a numerical value corresponding to the diagnostic datum.
- 57. (New) The method of claim 56, wherein the first web page further comprises multiple sets of diagnostic data associated with the single vehicle.
- 58. (New) The method of claim 55, wherein the first web page includes a graphical representation of a set of diagnostic data.

- 59. (New) The method of claim 52, wherein the web site further comprises a database component.
- 60. (New) The method of claim 52, wherein the web site further comprises a login web page programmed to accept user name and password inputs of a user.
- 61. (New) The method of claim 60, wherein the web site is configured to determine whether the user is associated with the first or second web interface.
- 62. (New) The method of claim 52, wherein the multiple vehicles are each associated with a single user.
- 63. (New) The method of claim 52, wherein the web site is configured to be displayed on a hand-held device.
- 64. (New) The method of claim 63, wherein the hand-held device comprises a cellular telephone, computer, or personal digital assistant (PDA).

- 65. (New) The method of claim 52, further comprising sending an electronic communication including at least a portion of the operational characteristics of the single vehicle or multiple vehicles.
- 66. (New) The method of claim 52, further comprising analyzing a location of the single vehicle and displaying the location on at least one map.
- 67. (New) The method of claim 52, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 68. (New) The method of claim 52, wherein the set of vehicles includes a fleet of vehicles.
 - 69. (New) A method of monitoring a set of vehicles, comprising:
 - (a) wirelessly transmitting, by a host computer, a schema,

wherein the schema identifies a subset of a set of operational characteristics that are monitorable by an on-board diagnostic computer of a target vehicle among a set of vehicles; and

- (b) wirelessly receiving collected vehicle data of the target vehicle, the collected data including the subset of monitorable operational characteristics identified in the transmitted schema.
- 70. (New) The method of claim 69, wherein the schema is associated with a predetermined group of vehicles.
- 71. (New) The method of claim 70, wherein the predetermined group of vehicles have at least one attribute in common.
- 72. (New) The method of claim 69, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 73. (New) A programmed apparatus, programmed to execute a method of monitoring a set of operational characteristics of a vehicle, the method comprising:
- (a) wirelessly receiving, by a wireless appliance in a vehicle, a schema identifying a subset of a set of operational characteristics that are monitored by an on-board diagnostic computer of the vehicle;

- (b) processing the received schema;
- (c) collecting from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema; and
 - (d) wirelessly transmitting the collected data.
- 74. (New) The programmed apparatus of claim 73, wherein the schema identifies an address of an operational characteristic for which data is to be collected from the vehicle's onboard diagnostic computer.
- 75. (New) The programmed apparatus of claim 73, wherein the method further comprises wirelessly transmitting data indicative of the vehicle's location.
- 76. (New) The programmed apparatus of claim 73, wherein the vehicle is selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 77. (New) A programmed apparatus, programmed to execute a method of monitoring a set of vehicles, the method comprising:
 - (a) wirelessly receiving, by a host computer, operational characteristics of a set of

vehicles;

- (b) displaying, on a first web interface of a web site, operational characteristics of a single vehicle selected from among said set of vehicles; and
- (c) displaying, on a second web interface of the web site, operational characteristics of multiple vehicles among said set of vehicles,

wherein said multiple vehicles are associated with a single entity.

- 78. (New) The programmed apparatus of claim 77, wherein the method further comprises wirelessly transmitting a schema identifying a subset of a set of operational characteristics to be monitored by an on-board diagnostic computer of a target vehicle.
- 79. (New) The programmed apparatus of claim 77, wherein the web site further comprises a login web page programmed to accept user name and password inputs of a user.
- 80. (New) The programmed apparatus of claim 77, wherein the method further comprises sending an electronic communication including at least a portion of the operational characteristics of the single vehicle or multiple vehicles.
 - 81. (New) The programmed apparatus of claim 80, wherein the set of vehicles

includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.

- 82. (New) A programmed apparatus, programmed to execute a method of monitoring a set of vehicles, the method comprising:
 - (a) wirelessly transmitting, by a host computer, a schema,

wherein the schema identifies a subset of a set of operational characteristics that are monitorable by an on-board diagnostic computer of a target vehicle among a set of vehicles; and

- (b) wirelessly receiving collected vehicle data of the target vehicle, the collected data including the subset of monitorable operational characteristics identified in the transmitted schema.
- 83. (New) The programmed apparatus of claim 82, wherein the schema is associated with a predetermined group of vehicles.
- 84. (New) The programmed apparatus of claim 82, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.

- 85. (New) A machine-readable medium encoded with a plurality of processor-executable instructions for:
- (a) wirelessly receiving, by a wireless appliance in a vehicle, a schema identifying a subset of a set of operational characteristics that are monitored by an on-board diagnostic computer of the vehicle;
 - (b) processing the received schema;
- (c) collecting from the vehicle's on-board diagnostic computer data for the subset of operational characteristics identified in the received schema; and
 - (d) wirelessly transmitting the collected data.
- 86. (New) The machine-readable medium of claim 85, wherein the vehicle is selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 87. (New) A machine-readable medium encoded with a plurality of processor-executable instructions for:
- (a) wirelessly receiving, by a host computer, operational characteristics of a set of vehicles;

- (b) displaying, on a first web interface of a web site, operational characteristics of a single vehicle selected from among said set of vehicles; and
- (c) displaying, on a second web interface of the web site, operational characteristics of multiple vehicles among said set of vehicles,

wherein said multiple vehicles are associated with a single entity.

- 88. (New) The machine-readable medium of claim 87, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 89. (New) A machine-readable medium encoded with a plurality of processor-executable instructions for:
 - (a) wirelessly transmitting, by a host computer, a schema,

wherein the schema identifies a subset of a set of operational characteristics that are monitorable by an on-board diagnostic computer of a target vehicle among a set of vehicles; and

(b) wirelessly receiving collected vehicle data of the target vehicle, the collected data including the subset of monitorable operational characteristics identified in the transmitted schema.

- 90. (New) The machine-readable medium of claim 89, wherein the set of vehicles includes at least one vehicle selected from a group comprising an automobile, truck, wheeled commercial equipment, heavy truck, power sport vehicle, collision repair vehicle, marine vehicle, and recreational vehicle.
- 91. (New) A graphical user interface for displaying monitored information of a set of vehicles, comprising:

a viewing device displaying a graphical user interface including,

- (a) a first web interface displaying wirelessly received operational characteristics of a single vehicle selected from among said set of vehicles; and
- (b) a second web interface displaying wirelessly received operational characteristics of multiple vehicles among said set of vehicles, wherein said multiple vehicles are associated with a single entity.
- 92. (New) The graphical user interface of claim 91, wherein the first web interface displays data fields describing: (i) a name of a diagnostic datum; (ii) units corresponding to the diagnostic datum; and (iii) a numerical value corresponding to the diagnostic datum.
- 93. (New) The graphical user interface of claim 92, wherein the first web interface further displays multiple sets of diagnostic data associated with the single vehicle.

- 94. (New) The graphical user interface of claim 91, wherein the first web interface includes a graphical representation of a set of diagnostic data.
- 95. (New) The graphical user interface of claim 91, wherein the displayed graphical user interface includes a web browser.
- 96. (New) The graphical user interface of claim 91, wherein the displayed graphical user interface is formatted using at least one wireless access protocol (WAP).
- 97. (New) The graphical user interface of claim 91, wherein the viewing device is one of a cellular telephone, a personal digital assistant (PDA), and a computer.